



**HOTMELT
SYSTEM**



One-Hand-Control
(Safety-Wheel)



Touch Display
(dust- & stain-resistant)



TANK

4 + 8 liter



HOSES

Connections 4



GUNS

perfectMelt SE

- New electronics
- New design
- One-Hand-Safety-Wheel-Control
- Intuitive colour touch display
- 4 + 8 liter tank
- 2 or 4 hose connections available
- Robatech / Fecu compatible
- Adjustable control of timer
- Clock timer

Technical specifications:




OPTIONAL

- WLAN-Connection
- Control via iPad-App
- Profibus & MODbus
- Pattern-Controller

Model	<i>perfectMelt SE</i>
Tank volumes	4/8 liter
Dimensions (H x W x T)	524 x 578 x 332 mm
Melting rate max.	4/8 liter/h
Delivery rate	30 liter/h
Pump	14 : 1 piston pump
Pressure range of pump	0,5 - 4,5 bar
Connections	2 or 4 channel hose connections
Surrounding temperature	5° C - 45° C
Temperature range	45° C - 195° C
Temperature sensor	Ni120 / NTC / PT100 / FeCu
Excess temp. shutdown	hardware thermostat
	adjustable software
Operating voltage	L/N/PE 230 V or 3L/N/PE 400V
Connection power of unit	2.200 W
External connection power	8.000 W

- Further options on request -

Your local partner



UES AG

Breuershofstraße 48

D-47807 Krefeld

Tel +49.2151.7295-0

Fax +49.2151.7295-78

info@ues-ag.net

www.ues-ag.net